

Spannscheiben DIN 6796

Belleville Washers DIN 6796



Spannscheiben DIN 6796 phosphatiert

Belleville Washers DIN 6796
phosphated



Ø D (mm)	Ø d (mm)	s (mm)	l ₀ (mm)	kg / %	
Ø D (mm)	Ø d (mm)	s (mm)	l ₀ (mm)	kg / %	
M 4,0	4,3	9	1,0	0,040	5.000
M 5,0	5,3	11	1,2	0,070	2.500
M 6,0	6,4	14	1,5	0,140	1.000
M 8,0	8,4	18	2,0	0,310	1.000
M 10,0	10,5	23	2,5	0,650	500
M 12,0	13,0	29	3,0	1,160	250
M 14,0	15,0	35	3,5	1,850	100
M 16,0	17,0	39	4,0	3,040	100
M 18,0	19,0	42	4,5	3,900	100
M 20,0	21,0	45	5,0	4,800	100
M 22,0	23,0	49	5,5	6,000	50
M 24,0	25,0	56	6,0	8,780	50
M 27,0	28,0	60	6,5	11,300	50
M 30,0	31,0	70	7,0	15,600	50

Spannscheiben DIN 6796 mechanisch verzinkt

Belleville Washers DIN 6796
mechanical plated



Ø D (mm)	Ø d (mm)	s (mm)	l ₀ (mm)	kg / %	
Ø D (mm)	Ø d (mm)	s (mm)	l ₀ (mm)	kg / %	
M 4,0	4,3	9	1,0	0,040	5.000
M 5,0	5,3	11	1,2	0,070	2.500
M 6,0	6,4	14	1,5	0,140	5.000
M 8,0	8,4	18	2,0	0,300	1.000
M 10,0	10,5	23	2,5	0,610	500
M 12,0	13,0	29	3,0	1,160	250
M 14,0	15,0	35	3,5	2,200	100
M 16,0	17,0	39	4,0	2,800	100
M 18,0	19,0	42	4,5	3,900	50
M 20,0	21,0	45	5,0	4,800	100
M 22,0	23,0	49	5,5	6,350	50
M 24,0	25,0	56	6,0	8,800	50
M 27,0	28,0	60	6,5	11,550	50
M 30,0	31,0	70	7,0	16,000	25