

Sprenggringe

Snap Rings



Sprengringe für Wälzanlagen

DIN 5417 SP

Snap Rings for Roller Bearings

DIN 5417 SP



Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SP 30	1,12	0,228	150
SP 32	1,12	0,242	150
SP 35	1,12	0,265	150
SP 37	1,12	0,309	150
SP 40	1,12	0,302	200
SP 42	1,12	0,214	200
SP 44	1,12	0,330	200
SP 47	1,12	0,400	100
SP 50	1,12	0,487	200
SP 52	1,12	0,507	200
SP 55	1,12	0,487	150
SP 56		0,543	150
SP 58		0,670	150
SP 62	1,70	0,899	100
SP 65	1,70	0,944	100
SP 68	1,70	1,248	100
SP 72	1,70	1,400	100
SP 75	1,70	1,303	100
SP 80	1,70	1,417	100
SP 85	1,70	1,750	100
SP 90	2,46	2,319	65
SP 95	2,46	2,435	65
SP 100	2,46	2,502	65
SP 110	2,46	2,934	65
SP 115	2,46	3,440	65
SP 120	2,82	5,564	60
SP 125	2,82	5,797	60
SP 130	2,82	5,800	60
SP 140	2,82	6,178	60
SP 145	2,82	7,300	60
SP 150	2,82	6,947	60
SP 160	2,82	7,414	60
SP 170	3,10	12,200	25
SP 180	3,10	12,800	25
SP 190		13,800	25
SP 200	3,10	14,800	25

Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SP 210	3,10	15,600	25
SP 215	3,10	16,000	25
SP 225	3,50	18,000	25
SP 230	3,50	23,500	25
SP 240			25
SP 250		22,000	25
SP 260			25
SP 270			25
SP 280			25
SP 290			25
SP 300			10

Sprengringe SW für Wellen

Snap Rings SW for Shafts



Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SW 16	1,2	0,071	1.000
SW 17	1,2	0,080	1.000
SW 18	1,2	0,075	1.000
SW 19	1,2	0,081	1.000
SW 20	1,2	0,084	1.000
SW 21	1,2	0,091	1.000
SW 22	1,2	0,091	1.000
SW 24	1,2	0,099	1.000
SW 25	1,2	0,100	500
SW 26	1,2	0,110	500
SW 27	1,5	0,229	500
SW 28	1,5	0,211	500
SW 29	1,5	0,220	500
SW 30	1,5	0,250	500
SW 32	1,5	0,410	250
SW 35	1,5	0,251	250
SW 37	1,5	0,294	250
SW 38	1,5	0,283	250
SW 40	1,5	0,303	125
SW 42	1,5	0,291	125
SW 43	1,5	0,325	125
SW 45	1,5	0,345	125
SW 47	1,5	0,361	125
SW 48	1,5	0,360	125
SW 50	1,5	0,385	125
SW 52	1,5	0,395	125
SW 55	1,5	0,422	125
SW 58	1,5	0,446	125
SW 60	1,5	0,452	125
SW 63	1,5	0,470	125
SW 65	1,5	0,497	125
SW 68	2,0	0,859	125
SW 70	2,0	0,900	100
SW 72	2,0	0,878	100
SW 73	2,0	0,890	100
SW 75	2,0	0,932	100

Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SW 80	2,0	1,000	100
SW 85	2,5	1,660	50
SW 90	2,5	1,760	50
SW 95	2,5	1,860	50
SW 100	2,5	1,760	50
SW 105	2,5	1,760	50
SW 110	2,5	2,160	50
SW 115	2,5	3,440	65
SW 120	2,5	2,310	50
SW 125	2,5	2,400	50
SW 130	2,5	2,550	50
SW 135	2,5	3,020	50
SW 140	2,5	3,480	50
SW 145	2,5	3,260	50
SW 150	2,5	3,500	50
SW 155	2,5	3,470	50
SW 160	2,5	3,690	50
SW 165	2,5	3,740	50
SW 170	2,5	3,920	50
SW 175	2,5	3,940	50
SW 180	3,0	6,500	50
SW 185	3,0	6,390	50
SW 190	3,0	6,590	50
SW 195	3,0	6,750	50
SW 200	3,0	7,275	50
SW 210	3,0	7,200	50
SW 220	3,0	7,500	50
SW 230	3,0	7,980	50
SW 240	3,0	8,170	50
SW 250	3,0	8,800	50

Sprengringe SW für Wellen

Snap Rings SW for Shafts



Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SW 260	4,0	17,900	25
SW 265		18,520	25
SW 270	4,0	19,770	25
SW 280		19,870	25
SW 285		19,950	25
SW 290	4,0	20,530	25
SW 300	4,0	21,420	25
SW 310	4,0	22,310	20
SW 330	4,0		20
SW 340	4,0	23,930	20
SW 350	4,0		25
SW 370	4,0		

Sprengringe SB für Wellen

Snap Rings SB for Shafts



Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SB 15	1,0	0,034	2.500
SB 16	1,2	0,059	1.000
SB 17	1,2	0,055	1.000
SB 18	1,2	0,068	1.000
SB 19	1,2	0,072	1.000
SB 20	1,2	0,085	1.000
SB 21	1,2	0,079	1.000
SB 22	1,2	0,081	1.000
SB 23	1,2	0,107	1.000
SB 24	1,2	0,090	500
SB 25	1,2	0,105	500
SB 26	1,2	0,098	500
SB 27	1,2	0,111	500
SB 28	1,2	0,113	500
SB 29	1,2	0,115	500
SB 30	1,5	0,202	125
SB 31	1,5	0,224	125
SB 32	1,5	0,225	125
SB 33	1,5	0,229	125
SB 34	1,5	0,238	125
SB 35	1,5	0,239	125
SB 37	1,5	0,260	125
SB 38	1,5	0,269	125
SB 39	1,5	0,279	125
SB 40	1,5	0,291	125
SB 42	1,5	0,304	125
SB 44	1,5	0,317	125
SB 45	1,5	0,322	125
SB 46	1,5	0,332	125
SB 47	1,5	0,335	125
SB 48	1,5	0,348	125
SB 50	1,5	0,350	125
SB 52	1,5	0,377	125
SB 53	1,5	0,382	125
SB 55	1,5	0,380	125
SB 57	1,5	0,423	125

Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SB 58	1,5	0,429	125
SB 60	1,5	0,443	125
SB 62	1,5	0,451	125
SB 63	1,5	0,450	125
SB 65	1,5	0,478	125
SB 68	1,5	0,514	125
SB 70	1,5	0,513	125
SB 72	2,0	0,850	100
SB 73	2,0	0,852	100
SB 74	2,0	0,900	100
SB 76	2,0	0,954	75
SB 78	2,0	0,905	75
SB 79	2,0	0,953	75
SB 80	2,0	1,000	75
SB 81	2,0	1,020	75
SB 82	2,0	0,945	75
SB 83	2,0	0,963	75
SB 85	2,0	1,000	75
SB 86	2,0	1,080	75
SB 88	2,0	1,540	75
SB 90	2,5	1,760	75
SB 92	2,5	1,700	75
SB 93	2,5	1,680	50
SB 95	2,5	1,800	50
SB 97	2,5	1,900	50
SB 98	2,5	1,750	50
SB 100	2,5	2,000	50
SB 102	2,5	1,890	50
SB 103	2,5	1,850	50
SB 105	2,5	2,010	50
SB 107	2,5	1,900	50
SB 108	2,5	1,930	50
SB 110	2,5	2,030	50
SB 112	2,5	2,030	50
SB 113	2,5	2,172	50
SB 115	2,5	2,200	50

Sprengringe SB für Wellen

Snap Rings SB for Shafts




Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SB 117	2,5	2,247	50
SB 118	2,5	2,257	50
SB 120	2,5	2,300	50
SB 123	2,5	2,303	50
SB 125	2,5	2,400	50
SB 127	2,5	2,409	50
SB 130	2,5	2,463	50
SB 133	2,5	2,172	50
SB 135	2,5	2,571	50
SB 137	2,5	2,800	50
SB 140	2,5	3,095	50
SB 143	2,5	3,100	50
SB 150	2,5	3,260	50
SB 153	2,5	3,400	50
SB 160	2,5	3,440	50
SB 163	2,5	3,460	50
SB 165	2,5	3,490	50
SB 170	2,5	3,500	50
SB 173	2,5	3,710	50
SB 175	2,5	3,730	50
SB 180	2,5	3,830	50
SB 183	2,5	4,100	50
SB 190	3,0	6,447	50
SB 195	3,0	6,160	50
SB 200	3,0	6,600	50
SB 205	3,0	6,600	50
SB 210	3,0	7,500	50
SB 215	3,0	6,950	50
SB 220	3,0	7,800	50
SB 225	3,0	8,290	50
SB 230	3,0	7,520	50
SB 240	3,0	8,272	50
SB 250	3,0	8,420	50
SB 260	4,0	16,500	25
SB 270	4,0	17,400	25
SB 280		18,400	25

Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
SB 290	4,0	20,000	25
SB 300	4,0	19,600	25
SB 310	4,0	21,600	25
SB 320	4,0	20,300	25
SB 325		20,600	25
SB 330	4,0	21,500	25
SB 340	4,0	21,900	25
SB 350	4,0	25,600	25
SB 360	4,0	24,000	10
SB 380	4,0		25
SB 400	4,0	28,400	25
SB 410	4,0	28,800	25
SB 440	4,0	31,200	25

Runddrahtsprengringe DIN 9926 RW für Wellen


Wire Snap Rings DIN 9926 RW for shafts



Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
RW 7	0,8	0,064	2500
RW 20	2,0	0,115	1000
RW 22	2,0	0,160	500
RW 25	2,0	0,184	500
RW 35	2,5	0,398	250
RW 38	2,5	0,460	250
RW 40	2,5	0,464	250
RW 45	2,5	0,464	250
RW 48	2,5	0,524	200
RW 50	2,5	0,583	200
RW 55	3,2	1,051	200
RW 60	3,2	1,150	200
RW 65	3,2	1,249	200
RW 70	3,2	1,340	200
RW 105	3,0	2,300	100

Runddrahtsprengringe DIN 9926 RB für Bohrungen

Wire Snap Rings
DIN 9926 RB for bores



Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
RB 4	0,6	0,018	2500
RB 5	0,6	0,022	2500
RB 6	0,6	0,380	2500
RB 7	0,8	0,043	2500
RB 8	0,8	0,009	2500
RB 10	0,8	0,011	2000
RB 12	1,0	0,021	1000
RB 14	1,0	0,025	1000
RB 16	1,6	0,074	1000
RB 18	1,6	0,083	1000
RB 20	2,0	0,145	1000
RB 22	2,0	0,160	500
RB 23	2,0	0,160	500
RB 24	2,0	0,178	500
RB 25	2,0	0,184	500
RB 26	2,0	0,179	500
RB 28	2,0	0,190	100
RB 30	2,0	0,210	500
RB 32	2,5	0,347	250
RB 33	2,5	0,347	250
RB 35	2,5	0,385	250
RB 38	2,5	0,385	250
RB 40	2,5	0,443	250
RB 45	2,5	0,489	200
RB 48	2,5	0,524	200
RB 50	2,5	0,551	200
RB 55	3,2	0,977	200
RB 60	3,2	1,076	100
RB 65	3,2	1,175	200
RB 70	3,2	1,244	200
RB 75	3,2	1,343	100
RB 80	3,2	1,442	100
RB 85	3,2	1,544	100
RB 90	3,2	1,640	100
RB 100	3,2	1,790	100
RB 105	3,2	1,898	100

Ø D (mm)	s (mm)	kg / %	
Ø D (mm)	s (mm)	kg / %	
RB 110	3,2	1,997	100
RB 120	3,2	2,195	100
RB 130	3,2	2,319	100