


Stützscheiben DIN 988

Support Washers DIN 988



Stützscheiben nach DIN 988


Support Washers DIN 988



Ø D (mm)	Ø d (mm)	s (mm)	kg / %	
Ø D (mm)	Ø d (mm)	s (mm)	kg / %	
SS 3	6	1,0	0,020	5000
SS 4	8	1,0	0,027	2000
SS 5	10	1,2	0,044	2500
SS 6	12	1,2	0,080	2000
SS 7	13	1,2	0,090	1000
SS 8	14	1,2	0,100	1000
SS 9	15	1,2	0,110	1000
SS 10	16	1,2	0,120	1000
SS 11	17	1,2	0,120	1000
SS 12	18	1,2	0,122	1000
SS 13	19	1,5	0,180	1000
SS 14	20	1,5	0,170	1000
SS 15	21	1,5	0,180	1000
SS 15	22	1,5	0,210	1000
SS 16	22	1,5	0,190	1000
SS 17	24	1,5	0,238	1000
SS 18	25	1,5	0,280	500
SS 19	26	1,5	0,290	500
SS 20	28	2,0	0,470	500
SS 22	30	2,0	0,510	500
SS 22	32	2,0	0,620	250
SS 25	35	2,0	0,740	250
SS 25	36	2,0	0,830	250
SS 26	37	2,0	0,860	250
SS 28	40	2,0	0,960	250
SS 30	42	2,5	1,244	50
SS 32	45	2,5	1,400	50
SS 35	45	2,5	1,142	50
SS 36	45	2,5	1,130	50
SS 37	47	2,5	1,290	50
SS 40	50	2,5	1,254	50
SS 42	52	2,5	1,450	50
SS 45	55	3,0	1,662	50
SS 45	56	3,0	1,906	50
SS 48	60	3,0	2,370	50
SS 50	62	3,0	2,200	50

Stützscheiben nach DIN 988

Support Washers DIN 988



Ø D (mm)	Ø d (mm)	s (mm)	kg / %	
Ø D (mm)	Ø d (mm)	s (mm)	kg / %	
SS 50	63	3,0	2,600	50
SS 52	65	3,0	2,624	50
SS 55	68	3,0	2,930	50
SS 56	70	3,0	3,270	50
SS 56	72	3,0	3,800	50
SS 60	75	3,0	3,700	50
SS 63	80	3,0	4,500	50
SS 65	85	3,5	6,300	50
SS 70	90	3,5	6,900	50
SS 75	95	3,5	7,320	50
SS 80	100	3,5	7,300	50
SS 85	105	3,5	8,200	50
SS 90	110	3,5	8,650	50
SS 95	115	3,5	9,070	50
SS 100	120	3,5	9,520	50
SS 100	125	3,5	12,200	50
SS 105	130	3,5	12,700	50
SS 110	140	3,5	15,624	50
SS 120	150	3,5	17,500	50
SS 130	160	3,5	18,800	50
SS 140	170	3,5	20,100	50
SS 150	180	3,5	21,400	50
SS 160	190	3,5	22,700	50
SS 170	200	3,5	24,000	50



**Ab 2,5 mm Dicke Seitenflächen geschliffen.
Einzeldickenabweichungen innerhalb der
Dickentoleranz.**

From 2.5 mm thickness, side surfaces are
ground. Individual thickness deviations are wit-
hin the thickness tolerance.